

The logo for Varcoll Paints features the word "VARCOL" in a large, bold, blue font with a white outline. Below it, the word "PAINTS" is written in a smaller, blue font. The logo is set against a blue and green background that forms a stylized 'V' shape. The word "DECORATIVE" is written vertically on the left side of the 'V', and "INDUSTRIAL" is written vertically on the right side.

PAINTS

DECORATIVE

INDUSTRIAL

BS RED OXIDE PRIMER

ALKYD PRIMER

PRODUCT CODE: 140-0020

DATA SHEET NO.:

SOLUTIONS FOR AFRICA

1. DESCRIPTION:

- Low cost, quick drying alkyd primer.

2. USES

- Primer for steel
- Bonding agent for subsequent undercoats and finishes

3. ADVANTAGES

- Can be applied by brush or spray
- Good adhesion to steel
- Quick drying
- Overcoatable with most finishing products
- Single pack

4. TECHNICAL DATA

- Color Red Oxide
- SG ± 1.22
- Viscosity 85 - 90 sec FORD CUP NO 4 AT 25°C
- Surface Dry ± 20 minutes @ 25°C
- Hard Dry ± 1 hour @ 25°C
- Solids $\pm 47\%$
- Thinners QD thinners (code 100-0001)
- Shelf Life 6 months from date of shipment in unopened original containers stored at temperatures below 30°C

5. SURFACE PREPARATION

- Surfaces must be clean, dry and free from oil, dirt and other contaminants
- Degrease with **TAKE OFF CLEANER (940-0002)**, a water-soluble degreasing solution. Rinse with clean water. Repeat cleaning until a water break free surface is obtained.
- Prepare steel by hand or power tool cleaning to grade St 3 of the International Standard ISO 8501-1: 1988.

6. APPLICATION

- Stir thoroughly before use
- Apply by airless or conventional spray
- Can be applied by brush

7. LIMITATIONS

- Not suitable for dip application
- Must not be exposed to rain, water or dew immediately after application
- Do not use where it can come into contact or immersion in acid or alkali

BS RED OXIDE PRIMER

ALKYD PRIMER

PRODUCT CODE: 140-0020

DATA SHEET NO.:

8. SAFETY PRECAUTIONS

- Product contains flammable materials, keep away from sparks and open flames.
- Refer to the MATERIAL SAFETY DATA SHEET (MSDS).

Disclaimer

The information contained herein is to the best of our knowledge correct and accurate and are meant to guide the specifier or user. Any recommendations or suggestions, which may be made, are without guarantee, since we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

Not all products referred to in these Data Sheets are stock items and are manufactured only on receipt of official customer orders. Thus, where time is of the essence, please check availability and manufacturing lead times with us.

VALIDITY DATE:

Paint Technology is continually being improved and developed. It is the user's responsibility to check that this sheet is current prior to using the product. We cannot accept ANY responsibility where this precaution has not been taken.

ISSUE DATE: 21-01-2005

DEVCOAT (PTY) LTD T/A VARCOL PAINTS:

8 MARCONI NOOK, HENNOSPARK EXT 15
P O BOX 8210, CENTURION, 0046
TEL: +27 12 653-0095 FAX: +27 12 653-0926
E-MAIL: devcoat @ netactive.co.za

