

**EFFECTIVE 1 OCTOBER 2013  
ROOF SHEETING**

Stock Code	Galvanised spec Grade & Quality		Corrugated 8½ (610mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
180 27XXX	Z100	ISQ550	Corrugated 8.5 (610mm coverage)	0.27	17.5	610	762	1.650	R 40.00
180 30XXX	Z100	ISQ550	Corrugated 8.5 (610mm coverage)	0.30	17.5	610	762	1.946	R 47.80

Stock Code	Galvanised spec Grade & Quality		Corr Widespan 10½ (762mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
181 30XXX	Z100	ISQ550	Corrugated 10.5 (762mm coverage)	0.30	17.5	762	925	2.230	POA
181 40XXX	Z150	ISQ300	Corrugated 10.5 (762mm coverage)	0.40	17.5	762	925	2.907	R 64.00
181 47XXX	Z150	ISQ550	Corrugated 10.5 (762mm coverage)	0.47	17.5	762	925	3.420	R 77.00
181 51XXX	Z275	ISQ550	Corrugated 10.5 (762mm coverage)	0.50	17.5	762	925	3.636	R 85.00
181 58XXX	Z275	ISQ300	Corrugated 10.5 (762mm coverage)	0.58	17.5	762	925	4.219	R 98.60
181 80XXX	Z275	ISQ230	Corrugated 10.5 (762mm coverage)	0.80	17.5	762	925	5.814	R 150.00

Stock Code	Galvanised spec Grade & Quality		IBR (686mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
182 30XXX	Z100	ISQ550	IBR (686mm coverage)	0.30	37	686	925	2.230	POA
182 40XXX	Z150	ISQ300	IBR (686mm coverage)	0.40	37	686	925	2.907	R 64.00
182 47XXX	Z150	ISQ550	IBR (686mm coverage)	0.47	37	686	925	3.420	R 77.00
182 51XXX	Z275	ISQ550	IBR (686mm coverage)	0.50	37	686	925	3.636	R 85.00
182 58XXX	Z275	ISQ300	IBR (686mm coverage)	0.58	37	686	925	4.219	R 98.60
182 80XXX	Z275	ISQ230	IBR (686mm coverage)	0.80	37	686	925	5.814	R 150.00

Stock Code	Galvanised spec Grade & Quality		IBR Widespan (762mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
183 30XXX	Z100	ISQ550	IBR Widespan (762mm coverage)	0.30	28.6	762	925	2.230	POA
183 40XXX	Z150	ISQ300	IBR Widespan (762mm coverage)	0.40	28.6	762	925	2.907	R 64.00
183 47XXX	Z150	ISQ550	IBR Widespan (762mm coverage)	0.47	28.6	762	925	3.420	R 77.00
183 51XXX	Z275	ISQ550	IBR Widespan (762mm coverage)	0.50	28.6	762	925	3.636	R 85.00
183 58XXX	Z275	ISQ300	IBR Widespan (762mm coverage)	0.58	28.6	762	925	4.219	R 98.60
183 80XXX	Z275	ISQ230	IBR Widespan (762mm coverage)	0.80	28.6	762	925	5.814	R 150.00

Stock Code	Chromadek spec		Corrugated Widespan 10,5 (762mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
	Grade & Quality								
184 47XXX	Z200	ISQ550	0.50mm chromadek COLOUR 1 SIDE	0.47	17.5	762	925	3.420	POA
184 50XXX	Z200	ISQ550	0.50mm chromadek COLOUR 1 SIDE	0.50	17.5	762	925	3.636	R 112.00
184 58XXX	Z200	ISQ300	0.58mm chromadek COLOUR 1 SIDE	0.58	17.5	762	925	4.219	R 125.00
184 80XXX	Z200	ISQ230	0.80mm chromadek COLOUR 1 SIDE	0.80	17.5	762	925	5.820	POA

Stock Code	Chromadek spec		IBR (686mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
	Grade & Quality								
184 347XX	Z200	ISQ550	0.58mm chromadek COLOUR 1 SIDE	0.47	37	686	925	3.420	POA
184 350XX	Z200	ISQ550	0.50mm chromadek COLOUR 1 SIDE	0.50	37	686	925	3.636	R 112.00
184 358XX	Z200	ISQ300	0.58mm chromadek COLOUR 1 SIDE	0.58	37	686	925	4.219	R 125.00
184 380XX	Z200	ISQ230	0.80mm chromadek COLOUR 1 SIDE	0.80	37	686	925	5.820	POA

Stock Code	Chromadek spec		IBR Widespan (762mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
	Grade & Quality								
184 447XX	Z200	ISQ550	0.50mm chromadek COLOUR 1 SIDE	0.47	28.6	762	925	3.420	POA
184 450XX	Z200	ISQ550	0.50mm chromadek COLOUR 1 SIDE	0.50	28.6	762	925	3.636	R 112.00
184 458XX	Z200	ISQ300	0.58mm chromadek COLOUR 1 SIDE	0.58	28.6	762	925	4.219	R 125.00
184 480XX	Z200	ISQ230	0.80mm chromadek COLOUR 1 SIDE	0.80	28.6	762	925	5.820	POA

Stock Code	Zincalume		Corrugated Widespan 10½ (762mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
	Grade & Quality								
184 147XX	AZ150	G550	ZINCALUME: 55% ALUMINIUM 45% GALV	0.47	17.5	762	914	3.333	POA
184 153XX	AZ150	G550	ZINCALUME: 55% ALUMINIUM 45% GALV	0.53	17.5	762	914	3.774	POA

Stock Code	Zincalume		IBR (686mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
	Grade & Quality								
184 047XX	AZ150	G550	ZINCALUME: 55% ALUMINIUM 45% GALV	0.47	37	686	914	3.333	POA
184 053XX	AZ150	G550	ZINCALUME: 55% ALUMINIUM 45% GALV	0.53	37	686	914	3.774	POA

Stock Code	Zincalume		Corrugated Widespan 10½ (762mm coverage)	Thickness mm	Flute height mm	Coverage mm	Coil width mm	Mass Kg/m	Rand metre
	Grade & Quality								
184 247XX	AZ150	G550	ZINCALUME: 55% ALUMINIUM 45% GALV	0.47	28.6	762	914	3.333	POA
184 253XX	AZ150	G550	ZINCALUME: 55% ALUMINIUM 45% GALV	0.53	28.6	762	914	3.774	POA

All prices are per metre excluding Vat  
All Widespan/Widek IBR have a stiffening rib rolled into the flat between the high flutes.